




ROHS2.0/HF/REACH

REV	ECN NO.	DETAILS	BY	DATE
1				



- Skills Requirement:
 1) a. 100%Open/Short test.
 b)DN-resistance: 3Ω (max).
 c)Insulation Resistance: 300V//DC 10MΩ(min).
 2) Electrical Characteristics:
 1)Rated Voltage (PIN Contact): 5Volts.
 2)Rated Current (PIN Contact): 0.5A.
 3)Insulation Resistance: 100MΩ min.
 4)Dielectric Withstand Voltage: 100V AT 60Hz.
 5)Contact Resistance: 30mΩ Max. Before Test And 60mΩMax. After Test.
 6)Press Stroke 10mm (Per Contact): 60±20gf
 7)Press stroke 10mm, 10,000 times Min.
 3)Salt Spray Test: 5% Salt Spray Concentration, Temperature 35°C, Test Time 48 Hours, No Corrosion.
 4)Working Temperature Range: -30~+85°C.
 5)PCT:ILC-P5MD075/12 肆肆 0.75A@25°C.Rmin=0.09R, Rmax=0.35R,Vmax=12V, (3SK/R)



Item	Part Name	Q'TY	Material	Finish	Remarks
8	External Molding Plastic	6g	TPE Material color: Black
7	Internal Molding Plastic	4g	PE Raw Material Color: Transparent
6	USB	1pcs	Black	Gold Plating
5	Cable	0.63m	TPE Black	∅3.0
4	PCB	1pcs	FR4	Lead free tin spraying
3	Magnet	2pcs	N48	Nickel 3.0um min plated
2	Pogo Pin	2pcs	HB159	Plunger Finish:Gold 3um Min Barrel Finish:Gold 3um Min
1	Housing	1pcs	ABS Black

*UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES
 LINEAR TOLERANCE:
 X±0.20 X+0.15 XX±0.10
 X*±2° X*±0.5°
 Pongtor
 Website:www.pongtor.net

POMAGTOR
 POGO PIN - 16 YEARS OF PROFESSIONAL
 Magnetic connection-professional for customization

TITLE	REV	SCALE	DATE	SHEET
USB A/M 70 HP2P-6磁吸线 黑色铜线L=0.6M	A0	1	21/11/20	1 of 2

DRAWN BY: **WBY** CHECKED BY: APPROVED BY: